



ENVIRONMENTAL:

1. Stotage :-40° 70+70°

- 2. Operation :-10° TO+60°**

1. SHIELD MATERIAL: ZINC ALLOY

- Fluke Test:Permanent Link ISO 11801 (PL 2)Class Ea
VOKA-LAN 500MHz CAT.6A Shielded Cable

RoHS 2.0 Compliant

⑦	MODULAR COVER	ZINC ALLOY	1	
⑥	RJ 45 INSERT	PHOSPHOR BRONZE 8P8C GOLD PLATED	8	
⑤	PCB	1.2mm UL 94V0	1	
④	IDC BODY	FIREPROOF/PC UL 94V0	1	
③	IDC PIN	PHOSPHOR BRONZE & TINNED	8	
②	LABEL COLOR CODE	T568A/B	2	
①	IDC TERMINAL	FOR 22-24AWG (0.45mm-0.65mm) CABLE	1	

NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK
		NEW		2019-09-09
BY		REVISION RECORD MODIFICATIONS		DATE

CUSTOMER				
PRODUCT NAME	CAT. 6A STP Plug			
DRAWNBY		CHECKBY	APPOBY	DATE
V.	WANG	LI		2019-09-09